

Goldhofer STZ-VL 3-33/80 A

Semi-trailers
FR 07/2008
Used vehicle

Price on request

More technical data

Vehicle Number GT4766
Construction Year 2008

Features

Air suspension
ABS

Vehicle Description

GOLDHOFER 3-axle low-bed semi-trailer STZ-VL 3-33/80 A

Maximum permissible laden weight: 24,000 kg
3 x 10t Axle load: 30,000 kg
Total weight: 54,000 kg
Tare weight: approx. 16,000 kg (without accessories)
Payload: approx. 38,000 kg

The following renewals are scheduled for 2024:

- Brakes completely overhauled
- All level cylinders have been replaced
- Central lubrication system has been overhauled
- Electrical system has been revised
- 2 tires replaced

- Gooseneck, hydraulic, with center beam
- Hydraulic lifting and lowering function incl. 2 outrigger cylinders
- Turning radius to the front: 1,245 mm / to the rear: 2,800 mm
- King pin: 3.5"
- Hydraulic connection for tractor unit
- Loading area 2,250 mm long at the front, reduced to 1,500 mm behind this, level with the lower edge of the swan neck support
- Hydraulic locking of the coupling claws of the special excavator bridge
- Multifunction quick coupling of the hydraulic connections

- special low bed in the form of an excavator bridge, welded directly onto the 3-axle chassis



additional frame reinforcement for driveability of track vehicles

- length: 7,800 mm, telescopic by 5,400 mm to 13,200 mm
- base width: 2,300 mm
- Overall height of the low bed bridge: 320 mm
- 3 special sliding tables, (1x table 2400 mm long, 2 x tables 1300 mm long) outer width of the tables 2,300 mm, with extension elements on all 3 tables for a max. outer width of 3,000 mm

• 3-axle chassis (air-suspended):

- Axle make: BPW Eco
- Axle compensation, hub 200 mm
- All three axles with hydraulic forced steering
- Chassis width: 2,550 mm
- Wheelbase 2 x 1,310 mm
- continuous excavator recess in the chassis; width 780 mm / length 4,100 mm
- twin tires 235/75R17.5
- easyControl "Comfort" self-steering for manual steering of the trailer axles using radio remote control and cable remote control
- frame spray-galvanized, RAL 6016 turquoise green

- SUBJECT TO THE INTERMEDIATE SALE -
- INFORMATION WITHOUT GUARANTEE -

Contact

Goldhofer Aktiengesellschaft
Johannes Fickler
Donaustraße 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-946
eMail: Johannes.Fickler@goldhofer.com

