

Goldhofer PST/ES-E 4 08x04 / PST/ES-E 6 12x04 / Power Pack PP 280/2400 Stage V

Heavy duty modules
FR 01/2024
Used vehicle

Price on request

More technical data

Vehicle Number AK 62536-62544
Construction Year 2023

Vehicle Description

GOLDHOFER Modular Heavy-Load Transport System with 9 components

3 units - Type PST/ES-E 4 08x04 (315)

- Weights:
 - 4 x 45 t axle load at 1 km/h
 - Tare weight (without accessories): approx. 16,900 kg
 - Payload: approx. 163,100 kg
- Dimensions:
 - Loading area length: 5,600 mm
 - Loading area width: 2,430 mm

4 pieces - Type PST/ES-E 6 12x04 (315)

- Weights:
 - 4 x 45 t axle load at 1 km/h
 - Tare weight (without accessories): approx. 24,500 kg
 - Payload: approx. 245,500 kg
- Dimensions:
 - Loading area length: 8,400 mm
 - Loading area width: 2,430 mm
- General features:
 - Chassis module combinable lengthwise and crosswise
 - Box-shaped center frame with integrated air tanks
 - High point loading in the area of the center tube and the closed outer fields
 - Front and rear bolt-tab couplings for



lengthwise combinations

- Oscillating axle units mounted on the vehicle frame by means of a rotary drive
- Tires: 315/60 R 22.5 (4 tires per axle line) Goodyear
- Hydraulic axle compensation +/-350 mm
- Safety valves to protect against hose rupture on all axle units
- Maximum steering angle +/-135 in all driving heights
- Electronic multi-way steering with different steering modes
- 2-line all-wheel air brake system with spring-loaded parking brake

2 x Power Pack PP - 280/2400 Stage V / T4F 36-19 / EU-Stage V
EPA-Tier 4F

- Weights:
 - Tare weight approx. 4,800 kg
- Dimensions:
 - Dimensions (L x W x H) 3,165 mm x 2,400 mm x 858 mm
- General features:
 - 6 cylinder in-line engine
 - Power 207 kW (280 HP)
 - 1 x removable auxiliary wheels for mounting on PST-Powerpack for storage and easier mobilization of the PST-Powerpack
 - 1 x radio remote control with emergency cable for PST-Powerpack with following functions: lifting/lowering, steering, incl. selection of different programs and changing the steering center
 - gear change
 - range 50m
 - cable length of emergency cable 10m
 - 1 x PST/SL-E and PST/ES-E emergency remote control, consisting of: cable remote control each for steering and drive in emergency operation
 - 1 x hydraulic locking bolt for attaching the PST Powerpack to the PST chassis
 - 1 x bumper with LED lighting, 2,400 mm wideSuitable for mounting on PowerPack PP-530/70-31 (3000) or PP-280/36-19 (2400)
Lighting system includes dipped beam and indicators

- SUBJECT TO INTERMEDIATE SALE -
- INFORMATION WITHOUT GUARANTEE -



GOLDHOFER AKTIENGESELLSCHAFT
Donaustrasse 95
87700 Memmingen/Germany

Tel.: +49 8331 15-0
Fax: +49 8331 15-239
Web: www.goldhofer.com

Contact

Goldhofer Aktiengesellschaft
Johannes Fickler
Donaustrasse 95
87700 Memmingen
Deutschland
Tel.: +49 8331 15-946
eMail: Johannes.Fickler@goldhofer.com